

100+ YEARS OF EUROPEAN
TRUST & COMMITMENT



Next Step To Future

TLX 20

2.0Ton Battery
Operated Pallet Truck



WHY BUY ME?

- ✓ High performance heavy duty BOPI in its class
- ✓ Safest stacker with operator guards, operator sensor platform & proximity sensors
- ✓ Easy to ride & maintain

TOLL FREE NUMBER- 1800 270 1123





BRAND HISTORY

- 1917** Founded in 1917; starts in 1918 the production of cars
- 1933** In 1933, acquisition by FIAT Group
- 1937** In 1937 The Plants Of Milan And Brescia Are Unified And The Agricultural Machinery Division Of Suzzarals Incorporated With The Growth Of 3 New Segments :
1.Buses, Trucks, 2.Rail Equipment, Agricultural Tractors, Forklift Trucks, Marine Engines
3.Engine Pumps And Cooling Systems
- 1957** In 1957 OM becomes FIAT Carrelli Elevatori, belonging to IVECO Division
- 1961** In 1961 PIMESPO, Piccola Industria Meccanica sul Po was born in Luzzara, manufacturing WH Trucks
- 1981** In 1981 FIAT IVECO acquires PIMESPO.
- 1992** In 1992 LINDE Group acquires from FIAT the Forklift Division.
- 2002** In 2002 the Company changes his name into OM Carrelli Elevatori keeping the Brand OM PIMESPO.
- 2005** In 2005 Luzzara becomes a Plant for the whole STILL Group
- 2006** In 2006 Linde, Still and OM are unified into the KION Group.
- 2017** In 2017, OM launched in Indian market.

OVERALL DIMENSIONS AND SPECIFICATIONS FOR TLX 20

CHARACTERISTICS	1.1 Manufacturer 1.2 Manufacturer model designation 1.3 Power unit 1.4 Operator type - Hand, Pedestrian, Standing, Seated, Order - picker 1.5 Load capacity 1.6 Load center distance 1.7 Load distance, center of load wheel to raised forks 1.8 Wheelbase	Q (kg) c (mm) x (mm) y (mm)	KION India TLX 20 Electric Standing 2000 600 872 1412
WEIGHT	2.1 Truck weight (with battery)	kg	770 (2)
WHEEL & TYRES	3.1 Tyre :rubber, pneumatic, polyurethane		Polyurethane
BASE DIMENSIONS	4.1 Lift height 4.2 Min / Max Height of tiller 4.3 Overall width 4.4 Outside fork width 4.5 Turning radius (Platform Closed / Open)	h3 (mm) h14 (mm) b1 (mm) b5 (mm) Wa (mm)	135 1220 / 1475 860 570 / 685 1732 / 2040
PERFORMANCE	5.1 Travel speed (Platform open) Loaded / Unloaded 5.2 Lift speed Loaded / Unloaded 5.3 Lowering speed Loaded / Unloaded 5.4 Max gradeability (S2 30 min) Loaded / Unloaded 5.5 Max gradeability (S2 5 min) Loaded / Unloaded 5.6 Service brake	km/h m/s m/s % %	6 / (6/6.7) ⁽¹⁾ 0,034 / 0,045 0,045 / 0,045 0.7 / 10 ^{(2) (3)} 4.5 / 12 ^{(2) (3)} Electric
E-MOTORS	6.1 Drive motor power 6.2 Lift motor power 15% ED 6.3 Battery voltage / capacity (5 hour rate) 6.3 Battery Compartment	kW kW V / Ah V / Ah	2.2 1.2 24 / (258) ⁽⁷⁾ 258Ah Standard
MISC	7.1 Steering		Manual



100+ CUSTOMER TOUCH POINTS FOR SALES & SERVICE



Address :
KION INDIA Private Limited, 5/4 Chaudan Nagar,
Pune Nagar, Road, Pune-411014
TOLL FREE NUMBER- 1800 270 1123